

NEW

UMKa315

A modern universal tracker that incorporates the main advantages of UMKa310, retains its compact size, RS-485, BLE interface and has a 250 mAh battery.



Advantages:

- Battery 250mAh;
- Impact-resistant housing of our own design, easy installation on ties;
- Optional - support for RS-485 interface for connecting up to 4 FLS;
- Controlling power modes using SMS commands;
- Possibility of connecting up to 3 FLS via BLE;
- Possibility of parallel sending of data to several servers;
- Management via DRC service;
- Housing protection degree - IP-54;
- MyLogic programming technology;
- Works as an iBeacon identification system;
- Lifetime warranty.



Li-ion



RS-485

MyLogic



iBeacon

BASE series

- ▶ 1 Analog input
- ▶ 1 digital input
- ▶ 2 digital inputs with pulse counting
- ▶ 1 Digital output
- ▶ Battery 250mAh in all trim levels
- ▶ Possibility of connecting up to 3 FLS
- ▶ EGTS support for data transfer to ERA-GLONASS
- ▶ MyLogic programming technology
- ▶ Built-in ceramic antenna
- ▶ Shockproof housing. Protection degree IP 54

Standard series

- ▶ 1 Analog input
- ▶ 1 Digital input
- ▶ 1 Digital output
- ▶ Support for RS-485 interface for connecting FLS
- ▶ Possibility of connecting up to 3 FLS
- ▶ EGTS support for data transfer to ERA-GLONASS
- ▶ Battery 250mAh in all trim levels
- ▶ MyLogic programming technology
- ▶ Built-in ceramic antenna
- ▶ Shockproof housing. Protection degree IP 54

